

REFRIGERATED DISPLAY 1500mm COUNTERSUNK

manufacturing SINCE 1966



Model: DFC2500



FEATURES


- Temperature range +2°C to +8°C at ambient temperature of 32°C
- Unit provided with 1 adjustable shelf
- LED illuminated shelf and base for perfect product presentation
- Digital display and temperature control for high accuracy
- Automatic defrost
- Low noise
- | Heated Tempered glass

- Grade 304 Stainless Steel interior
- Double glazed glass windows to prevent condensation
- Suitable for countersinking



THE CHEFS COMPANION

Model: DFC2500



SPECIFICATIONS

POWER
VOLTAGE
PACKAGING (W x D x H)
UNIT (W x D x H)
NET WEIGHT
GROSS WEIGHT
SHIPPING VOLUME
TEMPERATURE


CAPACITY SHELVES

AVAILABLE IN

0.47kW 230V - 50Hz 1620 x 570 x 845 (mm) 1500 x 470 x 680 (mm) 110kg 125kg 0.78m³ +2°C to +8°C at ambient temperature +32°C

118ℓ 2

✓ 120V/60Hz





NOTE

When viewing the appliance from the front in it's usual operating position, the width (W) of the product is the total distance from left to right; the depth (D) of the product is the total distance from the front to the back; the height (H) is the total distance from the bottom of the product to the top. Pictures may vary from actual product.

DISCLAIMER

Output performance figures quoted are dependent on various factors. Anvil reserves the right, without notice, to make changes and revisions to product specifications, materials and design, when we believe it will provide better performance, durability, and efficiency. Unit measurements may vary depending on point of reference.



www.anvilworld.com

Published Date: 2019.01.28