

REFRIGERATED DISPLAY 1500mm FLOOR STANDING

manufacturing SINCE 1966



Model: DFC7500



FEATURES


- Temperature range +2°C to +8°C ambient temperature of 32°c
- LED Illuminated shelf and base for perfect product presentation
- Castor wheels make the unit easy to move
- Digital display and temperature control for high accuracy
- Grade 304 stainless steel interior

- Unit provided with two adjustable shelves
- Automatic defrost
- Tempered heated glass
- Double glazed glass window to prevent condensation



THE CHEFS COMPANION

Model: DFC7500



SPECIFICATIONS

POWER
VOLTAGE
PACKAGING (W x D x H)
UNIT (W x D x H)
NET WEIGHT
GROSS WEIGHT
SHIPPING VOLUME
TEMPERATURE

CAPACITY SHELVES


AVAILABLE IN

0.923kW 230V - 50Hz 1585 x 765 x 1330 (mm) 1500 x 680 x 1200 (mm) 254kg 297kg 1.61m³ +2°C to +8°C at ambient

+2°C to +8°C at ambien temperature +32°C 500ℓ

3







NOTE

When viewing the appliance from the front in it's usual operating position, the width (W) of the product is the total distance from left to right; the depth (D) of the product is the total distance from the front to the back; the height (H) is the total distance from the bottom of the product to the top. Pictures may vary from actual product.

DISCLAIMER

Output performance figures quoted are dependent on various factors. Anvil reserves the right, without notice, to make changes and revisions to product specifications, materials and design, when we believe it will provide better performance, durability, and efficiency. Unit measurements may vary depending on point of reference.



www.anvilworld.com

Published Date: 2019.01.28